

# **IP KVM Matrix Extender**

# **User Manual**

www.kinankvm.com @all right reserved Shenzhen Kinan Technology Co., Ltd Print date: 2024 /06 Version: V3.2

# **User Information**

#### **Telephone Support**

For telephone support, please call below number:

TEL	0086-755-26755041
MOBILE	0086-13714411566

#### **User Notification**

All information, documentation, and specifications contained in this manual are subject to change without prior notice. The manufacturer does not make any explicit or implied statement or guarantee about the contents of this document, especially for merchantability or fitness for any specific purpose. Any manufacturer's equipment described in this manual is sold or licensed as it is.

If the equipment is damaged artificially after purchase, the buyer (not the manufacturer, its distributor or reseller) shall bear all costs for necessary repair and any losses caused by equipment defects.

If the correct operating voltage setting is not selected before operation, the manufacturer will not be responsible for any damage caused by system operation. **Please make sure the voltage has been set correctly before use**.

User Information Telephone Support	1 1
1. Introduction	3
1.1 Function	4
1.2 Feature	4
1.3 Safety Instructions	4
1.4 Product Overview	6
KFH151S sender (TX)	6
KFH151S receiver (RX)	7
2. Installation	8
2.1 Installation of Extender	8
3. Extender Configuration	10
3.1 Use of UI Interface	10
[Name Setting of TX_List]	11
[Auto Scan Setting]	12
[User Login Interface]	13
[The list of matched TX/RX]	13
3.2 Function Setting	14
[Equipment Info]	15
[Equipment Setting]	16
[Frame Push]	18
[Frame Get]	18
[Update]	20
[Hotkeys]	21
4. Specifications	22
Specifications of KFH151S	22

# 1. Introduction

The KFH151S IP KVM matrix extenders are highly optimized KVM extenders. The point-to-point connection supports transmission distance of 120m, and resolution up to 3840x2160@30Hz. This series of extenders can be connected to an 1G network switch to form a matrix switching system, which supports point-to-point (P2P) mode and matrix (Matrix) mode. The matrix switching system composed of extenders supports up to 9999 nodes by using a centralized management software, and it can support up to 40 nodes without using a centralized management software. It can connect multiple signal sources (such as servers, workstations, cameras and video walls).

With the matrix switching system, computers and servers can be located in the central server room far from the workstation to improve security, reduce the temperature and noise of the working environment, and achieve a quiet and friendly human-computer interaction environment.

The video compression algorithm of KFH151S matrix extender is a perfect combination of high-quality image and low latency (<16ms). The USB and video signals are transmitted through CAT5e/6/7 network cable.

It supports USB devices such as touch screen, USB sound card, printer, etc., it can also support USB storage devices.

#### 1.1 Function

This product is intended to be used as a device to increase the distance that a keyboard, monitor and mouse can be placed from a computer. This product is intended for professional use. The product should not be used in potentially explosive environments.

The product may only be used according to the instructions as described in this manual. All use, other than that described in this manual, is seen as unintended use. In this product, the product connected to the host end is called the transmitter (TX), and the product connected to the display end is called the receiver (RX).

#### 1.2 Feature

- HDMI / USB2.0/Audio/Rs232 IP KVM Matrix Extender
- Single and Dual screen version
- Point-to-point connection supports maximum extension distance 120m/394ft
- Can be connected to a standard network switch to form a matrix switching system
- Support seamless switching
- Freeze the last image after the disconnection of transmitter and receiver
- Support resolution up to 3840x2160@30Hz
- USB transmission rate up to 12MB/s
- HDMI lossless real-time full HD transmission
- Support local (TX) HDMI interface loop-out
- Support transmission through fiber optic and network (CAT5e/6/7)
- Support one Administrator account and one User account

#### 1.3 Safety Instructions

#### WARNING! Read and understand all safety instructions.

- Please follow all instructions. This will avoid accidents, fire, explosions, electric shocks or other hazards that may result in damage to property and/or severe or fatal injuries. Please ensure that everyone who uses the product has read and followed these warnings
- Keep all safety information and instructions for future reference and pass them on to subsequent users of the product.
- The manufacturer is not liable for cases of material damage or personal injury caused by incorrect handling or non-compliance with the safety instructions. In

#### IP KVM Matrix Extender

such cases, the warranty will be voided.

- The product is not allowed to use in potentially explosive environments.
- Check the product and the cables for any damage before use. If there is any visible damage, a strong odour, or excessive overheating of components unplug all the connections immediately and stop using the product.
- If the product is not installed and used in accordance with this manual, it may cause

disruptive interference with radio or television reception or affect other electronic products in residential areas.

- Use shielded cables to connect components to avoid the above interference.
- Only the power adapter included with the product should be used as the power supply. Do not use other adapters.
- Make sure your local voltage matches the rating indicated on the product before powering on it.
- The product must be connected to a permanent and earthed AC wall socket.
- Protect cables from being strained, pinched or buckled and place them in a way to prevent people from tripping over the cord.
- Avoid any damage to power adapter.
- Use the product with a suitable, properly installed and easily accessible power socket to make sure the product can be disconnected from the power socket at all times.
- Disconnect the product when not in use.
- Never touch the adapter with wet hands.
- Use the product within the specified performance limits.
- Keep the product away from any flammable materials like curtains.
- Protect the power adapter from use by third parties (particularly children).
- Keep the product away from heater.
- Do not drop or hit the product.

# 1.4 Product Overview

#### KFH151S sender (TX)



3	Rx Tx + ≟ - Pw		Serial Port
		PWR	Power indicator
4	150	SLED	System indicator
4		FIBER	Connection indicator of FIBER
		LINK	Connection indicator
5	AIN		Audio input
6	AOUT		MIC output
7	DBG		Debug interface
8	HDMI OUT		HDMI video loop out
9	HDMI IN		HDMI video input
10	USB IN		USB-B, connect to PC or server
11	DC1, DC2		Connect to the 12V power supply
12			Ground the device

#### KFH151S receiver (RX)

<b>III</b> Kinan					
RX () DBG () LEB 2.0 DEG () DC2 12V					
No.	Compone	nts	Description		
1	FIBER		Connection indicator		
2	LAN		Power indicator		
3	RJ11		Serial Port		
		PWR	Power indicator		
		SLED	System indicator		
4	LED	FIBER	Connection indicator of FIBER		
		LINK	Connection indicator		
5	<b>P</b>	1	MIC input		
6	(ا		Audio output		
7	DBG		Debug interface		
8	KEY		Reserved interfaces		
9	HDMI OUT		HDMI video output		
10	USB2.0		Connect to USB2.0 peripherals		
11			Connect to a USB keyboard		
12	[ <b>II</b> ]		Connect to a USB mouse		
13	DC1, DC2		Connect to the 12V power supply		
14			Ground the device		

#### 2. Installation

#### 2.1 Installation of Extender

Warning! Please read and be aware of all safety instructions before installing the equipment. The extender can be set as a point-and-point mode to access a single PC, and also can access multiple PCs through matrix switching system.

Matrix switching system



#### Connection Diagram of KFH151S



#### Matrix Connection Diagram



Configuration requirements: The electrical port of the network switch must reach a gigabit rate and support IGMP multicast.

#### 3. Extender Configuration

#### 3.1 Use of UI Interface

Press the left [Ctrl] key on the keyboard 3 times continuously, then the main UI interface will display.

2			RX-82220785f097		X
C	) 🎫 🗘				2×
SN		Tx-List		Status	QV
1		TX-02db0b1a6633		no video	
2		TX-0234b3616d6b		busy	
3		TX-02da799ae375		busy	
4		TX-02bf64e94952		connect	
5					
6					
7					
8					
9					
			Total TX:4		$\bigcirc$

Function Name	Description
Mode	Node Matrix P2P
	Scan device list
	The list of matched transmitter and receiver
\$	Setting of function key
2×	Click 【Equipment setting】 - 【User Setting Pass】 to logout user account
SN	Number of connected devices
TX_List	List of transmitters
Status	Busy: TX and RX are paired Busy : The RX has been connected to a TX No video: There is no video input from the host Connect: Can be connected
QV	Select Scan device
EQ	Find the devices in the list
	Auto Scan

# [Name Setting of TX\_List]

Double-click the name of a TX, and then the following name setting window appears.

2						×
Ċ	) 🎫	\$				2×
SN		Tx-List		Status		QV
1		TX-02db0b1a6633		no video		
2		TX-0234b3616d6b	Double-click to modify the name	busy		
3		TX-0234b3616d6b			×	
4		version:V7.5.11.18040CTX	TX-0234b36	16d6b		
5		MAC: 2:34:b3:61:6d:6b	Reboot:	ОК		
6		NID:169-254-39-57	Restore factory:	ОК		
7		ID:1462	Bit Rate:	Auto		
8		Frame Rate: Auto	NetworK mode:	Multicast		
9		3840x2160@60	EDID:	3840x2160 🔻		
í.		BID:2316-2316	Blink:	close 🗸		r_7
			Scan time:	10s 🗸		
		L				

Function Name	Description
Modify the name of a TX Modify the name of a TX Modify the name	
Reboot	Reboot the device
Restore factory	Restore Factory Defaults
Bit Rate	Auto, 10M ,50M, 100M, 150M, 200M
Network mode	Multicast mode Unicast mode
EDID	AUTO, 1024x768, 1280x1024, 1366x768,1600x900, 1920x1080,1920x1200,3840x2160
Blink	To set PWR flashing time, check TX connection status. You can choose from "Close, 1 min, 10 min, 30 min, 60 min, always".
Scan time 10s, 20s, 30s, 60s, 90s ,120s, 150s, 180s, 210s, 255s	

#### [Auto Scan Setting]

Select TX devices, click the QV item, and then click " 💽 " to automatically scan the selected device (default scan time: 10s).

2	admin	Mode: Matrix	RX-82220785f097		X
C	) 🎫 🗘				2×
SN		Tx-List		Status	QV
1		TX-02db0b1a6633		no video	Scan
2		TX-0234b3616d6b		busy	Scan
3		TX-02da799ae375		busy	Scan
4		TX-02bf64e94952		connect	Scan
5					
6					
7					
8					
9					
			Total TX:4		

Scan time: 10s, 20s, 30s, 60s, 90s, 120s, 150s, 180s, 210s, 255s

#### [User Login Interface]

The default setting m	node is " password mode:	(See User Sett	ting on Page 16), the
login interface will on	ly appear after clicking th	ne icon 🔼 🗙 .	
	UserName Password 1	ogin	
	User Name:	admin	
	Password:	admin	

#### [The list of matched TX/RX]

Click function key [ ] and then the following menu appears:

2		Mode: Matrix	RX-822	20785f097
				×
		ТХ		RX
	TX-02	2db0b1a6633		RX-826d9539bf91
	TX-02	234b3616d6b		
	TX-02	2da799ae375		RX-82220785f097
	TX-02	2bf64e94952		RX-82bcf4d41966

When you see the device name in the TX list and the RX list, that means that the TX and RX are matched successfully.

## **3.2 Function Setting**

Click the function key [, and then below menu appears:

💄 admin	Mode: Matrix RX-82220785f097	×
Operating mode	: Matrix	Equipment info
system state:	🗸 Usb 🗸 Audio 🗸 KM 🗸 S	hare Equipment setting
	Output timeing: 1080p@60	Frame push
	Total TX: 4 Total RX:2	
	MAC: 82:22:7:85:f0:97	Frame Get
	MID: 169-254-39-57	
	BID: 00000000000000	Update
	Version: V7.5.11.18040ERD	
		Hotkeys

Function Name	Description
Equipment Info	To switch on/off USB, Audio, KM, Get & Push
Equipment Setting	System and User Settings
Frame Push	Push the video and USB signals from current receiver to the chosen receiver in the list
Frame Get	Get the video and USB signals from any receiver in the list to the current receiver
Upgrade	Update device
Hotkey	Hotkeys of device

# [Equipment Info]

Select [] to switch on/off the system state.

💄 admin	Mode: Matrix RX-82220785f097	X
Operating mode	e: Matrix	Equipment info
system state:	🗸 Usb 🗸 Audio 🗸 KM 🗸 Share	Equipment setting
	Output timeing: 1080p@60 Total TX: 4 Total RX:2	Frame push
	Frame Get	
	Update	
		Hotkeys

Function Name	Description
Usb	USB function
Audio	Audio function
КМ	Keyboard and Mouse
Share	Push video & Get video

# [Equipment Setting]

💄 admin		RX-82220785f097		×
system Setting:				Equipment info
RX-82220785f	097	System mode:	Matrix	
Output timing:	1080p@60	NetworK mode:	Multicast	Equipment setting
Reboot:	ОК	Edid sync:	1920x1080	Frame nush
Restore factory:	ОК	All Blink:	close	
password mode:	•	-		Frame Get
				Update
				Hotkeys

Function Name	Description
RX-8220785f097	Click to change the name of RX, and then click "ESC" button to confirm your modification.
Output timing	Resolution 1080P@60, 1080P@50, 2160@30, 2160@25, 720P@60, 1366x768, 1440x900, 1920x1200, 1400x1050, AUTO PASS
Reboot	Reboot device
Restore factory	Restore factory defaults
System mode	Matrix mode P2P mode Node mode
Network mode	Multicast mode Unicast mode
Edid Sync	AUTO, 1024x768, 1280x1024, 1366x768, 1600x900, 1920x1080, 1920x1200, 2560x1440, 3840x2160
All Blink	To set PWR flashing time You can choose from "Close, 1 min, 10 min, 30 min, 60 min, always".
Password mode	Modify user name and set permissions

User Setting:

Click " • ", swipe right to " • ", and then the following menu appears. You can modify user password and set permissions.

You can't set the user name and password in Node mode, they can be set on the management control unit.

adı	min	Matrix	RX-82220785f097		×
system Set	ting:				Equipment info
RX-	82220785f	097	System mode:	Matrix	
Output tim	ning:	1080p@60	NetworK mode:	Multicast	Equipment setting
Reboot:		ОК	Edid sync:	1920x1080	Frame nush
Restore fac	ctory:	ОК	All Blink:	close	
password n	node: (	•	-		Frame Get
Name	Passwo	ord	Permissions		Undate
		🗸 U:	sb 🗸 Audi	o 🗸 KM	
admin	admin	🗸 sł	nare		Hotkeys
		<b>V</b> !	sb 🗸 Audio	o 🗸 KM	
user	user	SI	nare		

Function Name	Description		
Password Double click the name in the password list to m password of corresponding user.			
Permissions	Set permissions for USB, Audio, KM, Frame Get, and Frame Push.		

# IP KVM Matrix Extender

[Fram	ie Pusnj						
2				RX-82220785f09			×
SN		Rx-List			Push		
1		RX-826d9539	9bf91		Push		Equipment info
2		RX-824970a	75774		Push		Equipmont cotting
3	<u>lut</u> i	RX-82bcf4d4	1966		Push		Equipment setting
4							Frame push
5							· ·
6							Frame Get
7							
8							Update
9							Hotkova
10							поткеуз
11							
12						▼	

Click [Push] to push the video and USB signals from current receiver to the chosen receiver in the list.

#### [Frame Get]

2			RX-82220785f097			×
SN		Rx-List		Get		
1		RX-826d9539bf91		Get		Equipment info
2		RX-824970a75774		Get		Equipment setting
3	hit	RX-82bcf4d41966		Get		
4						Frame push
5						
6						Frame Get
7						
8						Update
9						Hatkova
10						поскеуз
11					_	
12					▼	

Click [Get] to get the video and USB signals from any receiver in the list to the current receiver.

#### Connection Diagram of Collaborative Sharing Push & Get



# [Update]



Click **[**RX**]** to update RX Click **[**TX**]** to update TX

# [Hotkeys]

💄 admin Matrix	RX-82220785f097	×
		Equipment info
Press the hotkey 3 time quie	ckly e Ul	Equipment setting
left Shift> Disconnect host right Ctrl> Next or previous	channels	Frame push
Switch hotkey		Frame Get
hold down right Ctrl+ double -cli	ck1-0> Switch from channel 1 to10	Update
		Hotkeys

Function Name	Description
Left _Ctrl	Shows or Hides the UI
Left_Shift	Disconnect host
Right_ Ctrl	Next or previous channels
Right_Ctrl+Doulbe 【1-0】	Switch from channel 1 to 10

# 4. Specifications

# Specifications of KFH151S

Specifications		KFH151S_TX	KFH151S_RX	
	HDMI input	1	N/A	
	HDMI output	1	1	
	Power	12V	12V	
	LAN port	RJ45 x 1	RJ45 x 1	
Connections	Optical Module	SFP+ x 1	SFP+ x 1	
	Mic	3.5MM Stereo Jack (Green)	3.5MM Stereo Jack (Pink)	
	Speaker	3.5MM Stereo Jack (Pink)	3.5MM Stereo Jack (Green)	
	Square USB	1	N/A	
	USB	N/A	USB x 4	
Resolution		3840x2160@30Hz		
Cable		CAT5e/6/7 or Optical Fiber Cable		
I/R Value		DC12V / 3A	DC12V / 3A	
Power consumption		6W	6W	
Operating ten	nperature	0—50 ℃		
Storage temp	erature	-20—60 °C		
Humidity		0—80% RH, non-condensing		
Material		Metal		
Net weight(kg	;)	0.7 kg 0.7kg		
Product dimension (W × D × H)		180mm x 123.5 mm x 44mm		
Package dimension (W × D × H)		243mmx 209mm x 98mm	243mmx 209mm x 98mm	